

## PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-157663

(43)Date of publication of application : 18.06.1996

(51)Int.Cl.

C08L 23/12

C08L 23/12

C08K 9/06

C08L 51/06

C08L 53/00

(21)Application number : 06-306213

(71)Applicant : MITSUBISHI CHEM CORP

(22)Date of filing : 09.12.1994

(72)Inventor : HIRAMATSU TAKESHI  
SOBASHIMA YOSHIHIRO  
SUZUKI OSAO

### (54) FIBROUS FILLER-REINFORCED RESIN COMPOSITION

(57)Abstract:

PURPOSE: To obtain a fibrous filler-reinforced resin composition excellent in mechanical strength balance, creep resistance, product appearance, etc.

CONSTITUTION: This fibrous filler-reinforced resin composition comprises 40-98wt.% of the below-described component (a), 2-60wt.% of the component (b), and the component (c) in an amount of (s) pts.wt. per 100 pts.wt. of the components (a) and (b), wherein the (s) pts.wt. satisfies a relation of  $qrs/p=k$  through a constant k of 0.2-3 between the content p (wt.%) of the component (b), the diameter  $q_{\mu m}$  of the fibrous filler and the maleic anhydride content r (wt.%) in the component (c). The component (a): a propylene homopolymer resin and/or a propylene-ethylene block copolymer resin having a melt flow rate of 1-500dg/min; the component (b): a fibrous filler whose surface is treated with a silane coupling agent; the component (c): a maleic anhydride-grafted propylene polymer having a maleic anhydride content of 3-12wt.% and obtained by subjecting a propylene polymer having a number-average mol.wt. of 5000-20000 and maleic anhydride to a grafting reaction condition.